

PWR™ SERIES WIRE: 3 PAIR

3 pair signal wire emulates Component Video

APPLICATIONS

- Receiver (Tuner)
- TVs: CRT, LCD, Plasma, or DLP
- DVD: Standard or High-Definition
- Cable or Satellite
- Gaming

COMPATIBLE WITH

- Component Video Wall Box

ADVANTAGES

- Installs on surface of walls and ceilings
- Easily concealed foil-thin wire that bends to any angle
- No special installation tools required
- Paintable insulation
- Disappears with paint or concealing compound & paint

FEATURES

- Pre-terminated wire ensures highest quality and easy installation via a snap fit
- Patented 'Pattern Wave Conductor' technology results in a uniquely formed length of copper wiring that transmits signals without any noticeable loss in the quality of picture or sound

SPECIFICATIONS

- Length: 10' & 20' (3m & 6m)
- Width: 1.700" (43.180mm)
- Thinness: 0.015" (0.381mm)
- Gauge: 28AWG or 12SEG (Skin Equivalent Gauge®)
- Oxygen Free Copper
- 6 Conductors (3 Pair)
- Resistance: 0.546 Ω (10')
- Capacitance: 18.700 pF/ft @ 100 KHZ
- Inductance: 0.200 μH/ft @ 100 KHZ
- Impedance: 75 Ω

